

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A22C 11/10	A1	(11) International Publication Number: WO 98/17119 (43) International Publication Date: 30 April 1998 (30.04.98)
(21) International Application Number: PCT/US97/18906 (22) International Filing Date: 20 October 1997 (20.10.97) (30) Priority Data: 60/028,910 21 October 1996 (21.10.96) US (71) Applicant: TOWNSEND ENGINEERING COMPANY [US/US]; 2425 Hubbell Avenue, Des Moines, IA 50317 (US). (72) Inventors: HERGOTT, Steven, P.; 2425 Hubbell Avenue, Des Moines, IA 50317 (US). SIMPSON, Michael, S.; 2425 Hubbell Avenue, Des Moines, IA 50317 (US). ENKLAAR, Rudolph, P.; 2425 Hubbell Avenue, Des Moines, IA 50317 (US). (74) Agent: ZARLEY, Donald, H.; Zarley, McKee, Thomte, Voorhees & Sease, Suite 3200, 801 Grand Avenue, Des Moines, IA 50309-2721 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: METHOD AND MEANS FOR LINKING SAUSAGE		
(57) Abstract A sausage making machine (10) has a meat pump (22), a twister with a chuck (30) to rotate a strand of sausage, a linker (32) to create links in the strand of sausage, a conveyor (38) with movable hooks to grasp loops in the sausage strand. Four separate motors (22A, 30A, 32A, 38A) are operatively connected to the pump (22), twister (30), linker (32) and conveyor (38), and the motors (22A, 30A, 32A, 38A) are all connected to and controlled by a computer (44) control having a memory with the operating parameters of the separate components. The method of operation involves imposing the operational parameters on the memory of the computer (44) to permit the computer (44) to control and coordinate the components (22A, 30A, 32A, 38A).		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

METHOD AND MEANS FOR LINKING SAUSAGE

BACKGROUND OF THE INVENTION

5 Sausage machines such as that shown in U.S. Patent No. 3,115,668 have a frame, a meat emulsion pump having metering gears to control meat emulsion flow; an elongated stuffing horn, a rotatable chuck, a linking device, a discharge horn and a conveyor with hooks thereon to carry linked product
10 away from the machine. In more recent times, separate motors are used to drive the pump, the twister (chuck), the linker, and the conveyor.

Previous linkers required the user to set-up the machine by specifying RPM's individually for each element in the
15 process (i.e. Pump, Linker, and Twister). There was no intuitive relationship which allowed the user to accurately benchmark these settings. Equations were provided in the operator's manual, but most users opted for a trial and error approach when performing this initial setup. Unfortunately,
20 this often resulted in lost time, bursted casings, and wasted materials.

In the past, the pump established the base speed for the system, and the linker speed was to make adjustments for weight.

25 Maintaining the weight of the linked product has heretofore been a cumbersome task, and often involved manual weighing steps and some trial and error compensation steps.

Prior encasing machines had no broad ranging readout means for sensing when maintenance to the machine was
30 necessary. As a result, needed maintenance is often overlooked.

It is therefore a principal object of this invention to provide a method and means for linking sausages that utilizes computer software and a computer display touch screen to use
35 a statistic approach to control the various phases of manufacturing sausages.

A further object of this invention is to control the pump, twister, linker and conveyor through four separate motors and through a computer which can coordinate their functions, and by using the linker motor as a master control
5 through the computer to control the remaining motors, to achieve a constant product feed rate.

A further object of this invention is to provide a method and means for linking sausage which can provide a straightforward, interactive fine tuning for weight control.

10 A further object of this invention is to provide a method and means for linking sausage which will monitor preventative maintenance schedules and signal their maturity to the operator.

A further object of this invention is to provide a
15 method and means for linking sausage which will provide a system for automatically downloading weights from a remote scale to a control system.

A still further object of this invention is to provide a method and means for linking sausage to provide a control
20 system that will minimize the number of filled links beyond a conveyor hook adjacent to the last full loop of linked products.

These and other objects will be apparent to those skilled in the art.

25

SUMMARY OF THE INVENTION

The device of this invention has four motors to drive the pump; the linking chains (linker); the twister and the conveyor. There are no mechanical linkages between motor
30 axes. The first three motors are "told" to go a certain speed by the PLC (computer), and operator, and there are no automatic checks to see that they are going the correct speed. Each motor is interdependent via a calculated ratio, based upon base speed of the linker chains motor. The motor
35 for the linker chains is the "master" of the machine. The speed of this motor is variable, but is viewed as the base

speed of the machine for ease of calculating the "links" per hour output.

The next most important motor in the machine is the metering pump motor. The speed of this motor is also
5 variable, but is initially set up as a calculated value. During normal running of the machine, an operator will determine if the "link" (hot dog/sausage) weight is too high or too little. If it is not the correct value, then the operator will use an "up" or "down" arrow key on the computer
10 to adjust the weight. By using these keys, the operator is actually adjusting the ratio of speed with respect to the linker of the pump motor. The value of speed that produces a correct weight "link" is stored in the computer, and the ratio of this speed to the "base" (linker) speed is also
15 stored.

The next motor is the "twister" motor. This spins the "chuck" and produces twists between links. The speed of this motor is variable, but will be initially set up as a calculated value. During normal running of the machine, an
20 operator will determine if there is enough twists between links or not. To change the number of twists the operator will use an "up" or "down" arrow key to increase the twist by 1/8 or decrease by 1/8. (This is really changing the ratio of speed with respect to the linker). The value of ratio
25 that produces the correct amount of twist is stored.

The fourth motor is the conveyor motor. It is a servo motor which means it is capable of very precise movements. It's speed, direction and move distance are not variable. It accelerates to a predetermined speed, to a predetermined
30 position and then decelerates to a predetermined position, zero speed. One motion profile available is called a triangle move, and takes approximately 1/3 of a second to complete.

The motors are interdependent. When the operator
35 changes the speed of the linking chains, this effects all the other motors in this way:

Pump motor: the previously stored ratio of base speed to pump speed is used to calculate a new pump motor speed.

Twister motor: the previously stored ratio of base speed to twister speed is used to calculate a new twister motor speed.

Conveyor motor: The increased linker speed increases the rate at which links are exiting the machine, hence, the frequency of the "triangle motion profile" must increase. This is in accordance to a predetermined number of counts derived from the linker chain driven shaft and a calculation of links in a loop between hooks.

The interdependency is important for maintaining weight control, twist control, and hanging of the finished product during consistent running speeds as well as when the production speed (base - linker chain) has been increased or decreased.

The new operator interface allows the user to perform this initial set-up by providing two parameters which are specified in a form that the operator can easily understand. These parameters are weight and length for the desired sausage link. Software in the machines programmable controller then uses these parameters to benchmark RPM's for each of the individual drives. The operator then simply uses item two to fine tune the product weight. Weight control for past linkers, as well as for the linker of this invention, is achieved by changing the speed relationship between the pump and linker. Previously the operator was required to understand the relationship between a change in a particular RPM and the resulting change in weight. The operator interface of this invention allows the operator to simply specify an incremental increase or decrease in weight. The software then executes the appropriate change in RPM.

In the past, the pump established the base speed for the system, and the linker speed was altered to make adjustments for weight. If feedrate is measured in number of links per unit time, then linker speed determines this rate. With this invention, the operator is not decreasing the feedrate when

he makes an adjustment for a loss in pump efficiency (i.e. a drop in mean weight of the product). This linker alters the relationship by establishing the linker as the base speed for the system.

5 Intervals for key maintenance activities are monitored by the control system and the operator is alerted when the interval for the required activity has been reached. For the pump this is tied to a measure of pump efficiency. For all other items it is tied to a specified number of run hours.
10 The specific length of the interval can be input by the user.

The operator interface on the linker of this invention will provide a system for automatically downloading weights from a remote scale into the linkers control system. Statistical analysis of the data along with graphical
15 charting can then be performed and displayed on the operator interface. This will facilitate better monitoring and decision making for the user.

The conveyor index rate defines the size of each sausage loop. Sometimes the strand length is just short of forming a
20 complete loop at the end of the strand. When this occurs, nearly a full loop of product dangles down from the conveyor. This dangling tail will often untwist. Once the sausage cell has untwisted, it becomes unusable as an accurately formed sausage. Minimizing the length of the dangling tail
25 optimizes utilization of casing and maximizes output in terms of links per strand. The linker of this invention can do a series of quicker indexes at the end of the strand. This will form one or more smaller loops which reduces the potential hanging tail after the last hook point.

30

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a front elevational view of the device of this invention;

Fig. 2 is a top plan view thereof;

35 Fig. 3 is an end elevational view as viewed from the right-hand end of Fig. 1;

Fig. 4 is a view of the device of Fig. 1 shown at a reduced scale with a conveyor attached to the outlet end thereof;

Fig. 5 is a top plan view of the device of Fig. 4;

5 Fig. 6 is a front elevational view similar to that of Fig. 1 but with the power train shown thereon;

Fig. 7 is a top plan view similar to that of Fig. 1 but also showing the power train imposed thereon;

10 Fig. 8 is an end elevational view similar to that of Fig. 3 but shows the power train imposed thereon;

Fig. 9 is a schematic drawing of the computer/motor control system; and

Figs. 10-20 are computer touch screen images.

15 DESCRIPTION OF THE PREFERRED EMBODIMENT

The numeral 10 comprises a sausage linker machine having a frame 12 which is comprised from front 14, and 16 and 18, and top 20.

20 A conventional emulsion pump 22 is mounted on frame 12 and is in communication with a conventional hollow elongated stuffing tube 26 through which the meat emulsion is moved by pump 22. An elongated follower arm 24 is mounted on the top of frame 12. A casing hopper 28 is mounted on the top of frame 12. A chuck 30 is mounted on the frame at the
25 discharge end of stuffing tube 26. A conventional set of linking chains 32 is mounted on frame 12 immediately downstream from chuck 30. Linked sausages move conventionally from the linking chains 32 through discharge tube 34 onto a conveyor 38 having a load cell 40 (scale).

30


A computer touch screen 42 (Fig. 9) is operatively secured to a PLC 44 (Fig. 9). Typical screen images appear in Figs. 10-20.

We claim:

1. A method of controlling the output of a sausage encasing machine having a pump, a twister, and a linker, each powered
5 by one of three separate motors, comprising, interconnecting said motors to a computer control having a memory, imposing on said computer the parameters of a linked product as to length and weight, operating said machine to produce a linked
10 product in accordance with said parameters, and adjusting the speed of the motor connected to said linker to cause a corresponding change in the motors connected to said pump and said twister to compensate for any variance of such linked product with respect to said parameters.
- 15 2. A method of claim 1 comprising the further step of measuring a linked product so produced to ascertain any variance of such linked product with respect to said parameters,
- 20 3. A linker machine comprising a pump, a twister, and a linker, each powered by one of three separate motors, a computer operatively connected to said three motors, first control means on said computer for permitting the motors connected to said pump and said twister motor to be
25 separately and independently controlled, and second control means connected to said three motors whereby a change of speed imposed upon said linker motor will cause a corresponding change in speed in said pump and twister motors.
- 30 4. The device of claim 3 wherein said machine includes a conveyor having a motor, said conveyor motor being linked electronically to said linker motor.
- 35 5. The device of claim 3 wherein said machine has a plurality of moving parts, means associated with said parts to measure the magnitude of use of said parts, said means

connected to said computer to visually indicate that maintenance is required when the magnitude of use of said party reaches a predetermined level.

1/15



2/15




FIG. 5








FIG. 4



4/15



5/15




FIG. 10

6/15




FIG. 11

7/15




FIG. 12

8/15




FIG. 13

9/15




FIG. 14

10/15




FIG. 15

11/15




FIG. 16

12/15

Preventative Maintenance		Townsend HL SmartLinker	
0	10 S	0	4000 HRS
0	1000 HRS	0	1000 HRS
0	2000 HRS	0	4000 HRS

--	--	--	--	--	--	--	--

FIG. 17

13/15




FIG. 18

14/15




FIG. 19

15/15




FIG. 20

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 97/18906

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A22C11/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A22C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 395 177 A (HITEC CO LTD) 31 October 1990 see claim 1 ---	1,3
A	EP 0 250 733 A (SCHNELL MASCHFAB KARL) 7 January 1988 see page 4, line 13 - page 5, line 7; claims 15-18 ---	1-3
A	WO 96 05733 A (TOWNSEND ENGINEERING CO) 29 February 1996 see claims 2-6, 10, 11 ---	1-3
A	US 3 694 853 A (GREIDER CHARLES AUSTIN) 3 October 1972 see claim 18; figure 10 ---	1,3,4
-/--		



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

25 February 1998

Date of mailing of the international search report

05/03/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

De Lameilleure, D

INTERNATIONAL SEARCH REPORT

Int. Patent Application No.

PCT/US 97/18906

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 476 258 A (HANDTMANN ALBERT MASCHF) 25 March 1992 see column 2, line 28 - line 52 see column 4, line 20 - line 25; claim 7 ---	1,3,4
A	EP 0 439 671 A (HANDTMANN ALBERT MASCHF) 7 August 1991 ---	
A	FR 2 620 902 A (CABY JEAN & CIE SARL) 31 March 1989 ---	
A	EP 0 392 083 A (HANDTMANN ALBERT MASCHF) 17 October 1990 -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/18906

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0395177 A	31-10-90	JP 2286036 A JP 2612491 B DE 69005509 D DE 69005509 T ES 2048414 T US 5092813 A	26-11-90 21-05-97 10-02-94 01-06-94 16-03-94 03-03-92
EP 0250733 A	07-01-88	DE 3617560 A CA 1265382 A DK 260587 A ES 2030009 T JP 63033206 A US 4823439 A	26-11-87 06-02-90 25-11-87 16-10-92 12-02-88 25-04-89
WO 9605733 A	29-02-96	AU 3324895 A AU 3420397 A CA 2203797 A EP 0722271 A	14-03-96 30-10-97 29-02-96 24-07-96
US 3694853 A	03-10-72	NONE	
EP 0476258 A	25-03-92	DE 4028343 A AT 112455 T CA 2045439 A CS 9102324 A DE 59103166 D ES 2061127 T JP 2071494 C JP 4281735 A JP 7112400 B US 5147239 A	12-03-92 15-10-94 07-03-92 18-03-92 10-11-94 01-12-94 10-07-96 07-10-92 06-12-95 15-09-92
EP 0439671 A	07-08-91	DE 9001076 U CA 2030647 A DE 59003706 D ES 2047215 T JP 2015441 C JP 5344835 A JP 7046960 B US 5083970 A	30-08-90 01-08-91 13-01-94 16-02-94 02-02-96 27-12-93 24-05-95 28-01-92

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/18906

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR 2620902 A	31-03-89	NONE	
EP 0392083 A	17-10-90	DE 3911859 A	18-10-90
		CA 2011105 A	11-10-90
		CS 9001530 A	13-08-91
		JP 2268638 A	02-11-90
		JP 7057157 B	21-06-95
		SU 1829900 A	23-07-93
		US 5049108 A	17-09-91